



## Sizing Chart: Gallium Pro 2018

Saddle Height	Suggested Size	A	B	C	D	C	D	C	D	E	
		Seat Tube Angle	Top Tube Length	Stack 3D Spacer = 0	Reach	Stack 3D Spacer = 15	Reach	Stack 3D Spacer = 25	Reach	Minimum Drop	Maximum Drop
61	XXS	75.5	499	474	374	488	369	498	366	-4	-53
62	XXS	75.5	499	474	374	488	369	498	366	-14	-63
63	XXS	75.5	499	474	374	488	369	498	366	-23	-73
64	XXS	75.5	499	474	374	488	369	498	366	-33	-82
65	XXS / XS	75.5 / 74.5	499 / 519	474 / 492	374 / 382	488 / 506	369 / 377	498 / 516	366 / 374	-43 / -23	-92 / -73
66	XXS / XS	74.5	499 / 519	474 / 492	374 / 382	488 / 506	369 / 377	498 / 516	366 / 374	-52 / -33	-102 / -82
67	XS	75.5	519	492	382	506	377	516	374	-42	-92
68	XS	75.5	519	492	382	506	377	516	374	-52	-101
69	XS / S	74.5 / 74	519 / 539	492 / 523	382 / 389	506 / 537	377 / 384	516 / 547	374 / 381	-62 / -28	-111 / -77
70	XS / S	74.5 / 74	519 / 539	492 / 523	382 / 389	506 / 537	377 / 384	516 / 547	374 / 381	-71 / -37	-121 / -87
71	S	74	539	523	389	537	384	547	381	-47	-96
72	S	74	539	523	389	537	384	547	381	-56	-106
73	S / M	74 / 73.5	539 / 559	523 / 552	389 / 395	537 / 566	384 / 391	547 / 575	381 / 388	-66 / -34	-115 / -83
74	S / M	74 / 73.5	539 / 559	523 / 552	389 / 395	537 / 566	384 / 391	547 / 575	381 / 388	-76 / -43	-125 / -93
75	M	73.5	559	552	395	566	391	575	388	-53	-102
76	M	73.5	559	552	395	566	391	575	388	-62	-112
77	M / L	73.5 / 73	559 / 577	552 / 575	395 / 401	566 / 590	391 / 396	575 / 599	388 / 394	-72 / -44	-122 / -94
78	M / L	73.5 / 73	559 / 577	552 / 575	395 / 401	566 / 590	391 / 396	575 / 599	388 / 394	-82 / -54	-131 / -103
79	L	73	577	575	401	590	396	599	394	-63	-113
80	L	73	577	575	401	590	396	599	394	-73	-123
81	L / XL	73 / 72.5	577 / 596	575 / 596	401 / 408	590 / 610	396 / 404	599 / 620	394 / 401	-83 / -59	-132 / -108
82	L / XL	73 / 72.5	577 / 596	575 / 596	401 / 408	590 / 610	396 / 404	599 / 620	394 / 401	-92 / -68	-142 / -118
83	XL	72.5	596	596	408	610	404	620	401	-78	-128
84	XL	72.5	596	596	408	610	404	620	401	-87	-137
85	XL	72.5	596	596	408	610	404	620	401	-97	-147

This chart indicates recommended values. Max and min drop values are calculated according to Canadian specifications. Please consult one of our authorized dealers for further informations on your bike fit.



**ARGON 18**